




DP-RMSP-DP15

DOPEY

Luminaire Information

System power	15W
CCT	2700K, 3000K, 4000K, 5000K, 6000K
CRI / Ra	±90Ra
Fixture lumen output	2100lm
Material	Aluminum
Surface finish	Powder coating
Optics	Reflector (15°, 24°, 38°)
UGR level	<19
Installation	Recessed
IP rate	IP54
Fixture	Fixed

Product Dimension



Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	350mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option



Light Throw

DP-RMSP-DP15	3000K	90Ra																		
	h(m)	E(lx)	D(cm)																	
	1	2906	31		<table border="1"> <thead> <tr> <th>h(m)</th> <th>E(lx)</th> <th>D(cm)</th> </tr> </thead> <tbody> <tr><td>1</td><td>1748</td><td>43</td></tr> <tr><td>2</td><td>437</td><td>86</td></tr> <tr><td>3</td><td>194</td><td>130</td></tr> <tr><td>4</td><td>109</td><td>173</td></tr> </tbody> </table>	h(m)	E(lx)	D(cm)	1	1748	43	2	437	86	3	194	130	4	109	173
	h(m)	E(lx)	D(cm)																	
	1	1748	43																	
	2	437	86																	
3	194	130																		
4	109	173																		
2	726	63																		
3	322	94																		
4	181	126																		
	1	826	70	<table border="1"> <thead> <tr> <th>h(m)</th> <th>E(lx)</th> <th>D(cm)</th> </tr> </thead> <tbody> <tr><td>1</td><td>826</td><td>70</td></tr> <tr><td>2</td><td>206</td><td>140</td></tr> <tr><td>3</td><td>91</td><td>210</td></tr> <tr><td>4</td><td>51</td><td>281</td></tr> </tbody> </table>	h(m)	E(lx)	D(cm)	1	826	70	2	206	140	3	91	210	4	51	281	
	h(m)	E(lx)	D(cm)																	
	1	826	70																	
	2	206	140																	
3	91	210																		
4	51	281																		
2	206	140																		
3	91	210																		
4	51	281																		