

RECESSED MOUNTED SPOTLIGHT


COMMERCIAL

DEEPA®



DP-RMSC-FR10-2

Product Dimension



FORCE

Luminaire Information

System power	2*10W
CCT	2700K, 3000K, 3500K, 4000K, 5000K
CRI / Ra	±90Ra / ±95Ra
Fixture lumen output	2*700lm
Material	Aluminum
Surface finish	Textured powder coating
Optics	Lens (15°, 24°, 36°, 45°)
UGR level	<19
Installation	Recessed
IP rate	IP20
Fixture	Adjustable

Light Engine Information

LED type	COB
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	2*250mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI / BLUETOOTH

Color Option




Black White


Light Throw

DP-RMSC-FR10-2 3000K 90Ra


h(m)	E(lx)	D(cm)
1	2961	33
2	740	66
3	329	98
4	185	131



h(m)	E(lx)	D(cm)
1	2220	44
2	555	87
3	247	131
4	139	174



h(m)	E(lx)	D(cm)
1	1137	63
2	284	127
3	126	190
4	71	253



h(m)	E(lx)	D(cm)
1	776	82
2	194	163
3	86	245
4	49	326

