




**DP-TSRC-GM20**

**Product Dimension**



**GAMA**

**Luminaire Information**

System power	20W
CCT	27000K, 3000K, 4000K, 5000K
CRI / Ra	±90Ra
Fixture lumen output	1600lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (15°, 24°, 38°)
UGR level	<17
Installation	Track mounted
IP rate	IP20
Fixture	Fixed

**Light Engine Information**

LED type	COB (SANAN)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

**Driver Information**

Driver type	Built-in
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	500mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI


**Color Option**




**Light Throw**

DP-TSRC-GM20 3000K 90Ra

	h(m)	E(lx)	D(cm)
1	1	4492	45
2	2	1123	91
3	3	499	137
4	4	280	183



	h(m)	E(lx)	D(cm)
1	1	3564	54
2	2	890	109
3	3	396	164
4	4	222	219



	h(m)	E(lx)	D(cm)
1	1	2070	82
2	2	517	164
3	3	230	247
4	4	129	329

