




DP-TSRC-GM30

GAMA

Luminaire Information

| | |
|----------------------|-----------------------------|
| System power | 30W |
| CCT | 27000K, 3000K, 4000K, 5000K |
| CRI / Ra | ±90Ra |
| Fixture lumen output | 2700lm |
| Material | Aluminum |
| Surface finish | Powder coating |
| Optics | Lens (15°, 24°, 38°) |
| UGR level | <17 |
| Installation | Track mounted |
| IP rate | IP20 |
| Fixture | Fixed |

Product Dimension



Light Engine Information

| | |
|-------------|-----------------|
| LED type | COB (SANAN) |
| LED voltage | 36V |
| SDCM | 2 SDCM / 3 SDCM |

Driver Information

| | |
|----------------|-------------------------------|
| Driver type | Built-in |
| Input voltage | 220-240 VAC |
| Output voltage | 30-42 VDC |
| Output current | 700mA |
| Dimming system | ON-OFF / TRIAC / 1-10V / DALI |


Color Option




Light Throw

DP-TSRC-GM30 3000K 90Ra

| h(m) | E(lx) | D(cm) |
|------|-------|-------|
| 1 | 6987 | 37 |
| 2 | 1747 | 74 |
| 3 | 776 | 111 |
| 4 | 436 | 148 |



| h(m) | E(lx) | D(cm) |
|------|-------|-------|
| 1 | 5467 | 47 |
| 2 | 1367 | 95 |
| 3 | 607 | 142 |
| 4 | 314 | 190 |



| h(m) | E(lx) | D(cm) |
|------|-------|-------|
| 1 | 3488 | 64 |
| 2 | 871 | 134 |
| 3 | 387 | 201 |
| 4 | 218 | 268 |

