




**DP-SMP-LCS22**

## LUCCI SURFACE

### Luminaire Information

System power	22W
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, TW
CRI / Ra	±95Ra
Fixture lumen output	1800lm
Material	Aluminum
Surface finish	Textured powder coating
Optics	Reflector (24°, 36°, 45°)
UGR level	<10
Installation	Surface mounted
IP rate	IP20

### Product Dimension




### Light Engine Information

LED type	SMD 3535
LED voltage	30V
SDCM	3 SDCM / 5 SDCM

### Driver Information

Driver type	Built-in driver
Input voltage	220-240 VAC
Output voltage	27-33 VDC
Output current	700mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

### Accessories




### Color Option




### Light Throw

DP-SMP-LSS22 3000K 90Ra

	h(m)	E(lx)	D(cm)
1	5750	39	
2	1437	79	
3	638	119	
4	359	159	



	h(m)	E(lx)	D(cm)
1	3163	64	
2	790	129	
3	351	193	
4	197	258	



	h(m)	E(lx)	D(cm)
1	2308	75	
2	576	151	
3	256	226	
4	144	302	

