




DP-RMSA-LN10

## LUNA

### Luminaire Information

System power	10W
CCT	2700K, 3000K, 3500K, 4000K
CRI / Ra	±95Ra
Fixture lumen output	880lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (10°, 15°, 24°, 36°, 55°)
UGR level	<19
Installation	Recessed
IP rate	IP65
Fixture	Adjustable

### Product Dimension



### Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

### Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	250mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI


### Color Option




### Light Throw

DP-RMSA-LN10 3000K 95Ra


h(m)	E(lx)	D(cm)
1	3805	29
2	951	59
3	422	89
4	237	119



h(m)	E(lx)	D(cm)
1	2505	43
2	626	87
3	278	131
4	156	175



h(m)	E(lx)	D(cm)
1	1230	65
2	307	131
3	136	196
4	76	262



h(m)	E(lx)	D(cm)
1	496	105
2	124	210
3	55	315
4	31	420