




DP-RMSA-LN12

LUNA

Luminaire Information

System power	12W
CCT	2700K, 3000K, 3500K, 4000K
CRI / Ra	±95Ra
Fixture lumen output	1056lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (10°, 15°, 24°, 36°, 55°)
UGR level	<19
Installation	Recessed
IP rate	IP65
Fixture	Adjustable

Product Dimension



Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	300mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option



Light Throw

DP-RMSA-LN12 3000K 95Ra			DP-RMSA-LN12 3000K 95Ra			DP-RMSA-LN12 3000K 95Ra			DP-RMSA-LN12 3000K 95Ra		
h(m)	E(lx)	D(cm)	h(m)	E(lx)	D(cm)	h(m)	E(lx)	D(cm)	h(m)	E(lx)	D(cm)
1	3805	29	1	2505	43	1	1230	65	1	496	105
2	951	59	2	626	87	2	307	131	2	124	210
3	422	89	3	278	131	3	136	196	3	55	315
4	237	119	4	156	175	4	76	262	4	31	420