




DP-RMSA-LN8

## LUNA

### Luminaire Information

System power	8W
CCT	2700K, 3000K, 3500K, 4000K
CRI / Ra	±95Ra
Fixture lumen output	576lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (10°, 15°, 24°, 36°, 55°)
UGR level	<19
Installation	Recessed
IP rate	IP65
Fixture	Adjustable

### Product Dimension



### Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

### Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	180mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

### Color Option



### Light Throw

DP-RMSA-LN8 3000K 95Ra

	h(m)	E(lx)	D(cm)
15°	1	3805	29
	2	951	59
	3	422	89
	4	237	119

	h(m)	E(lx)	D(cm)
24°	1	2505	43
	2	626	87
	3	278	131
	4	156	175

	h(m)	E(lx)	D(cm)
36°	1	1230	65
	2	307	131
	3	136	196
	4	76	262

	h(m)	E(lx)	D(cm)
55°	1	496	105
	2	124	210
	3	55	315
	4	31	420