




DP-RMSP-MC10

MACA


Luminaire Information

System power	10W
CCT	2700K, 3000K, 3500K, 4000K, TUNABLE WHITE
CRI / Ra	≥90Ra
Fixture lumen output	600lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (15°, 24°, 36°)
UGR level	<14
Installation	Recessed
IP rate	IP20 / IP54
Fixture	Adjustable

Product Dimension



DP-RMSP-MC10
Fixed



DP-RMSP-MC10(TL)
Trimless

Light Engine Information

LED type	COB
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	180mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option



Black White

Light Throw

DP-RMSP-MC10 3000K 90Ra

	h(m)	E(lx)	D(cm)
1	2906	31	
2	726	63	
3	322	94	
4	181	126	

15°

	h(m)	E(lx)	D(cm)
1	1748	43	
2	437	86	
3	194	130	
4	109	173	

24°

	h(m)	E(lx)	D(cm)
1	826	70	
2	206	140	
3	91	210	
4	51	281	

36°

	h(m)	E(lx)	D(cm)
1	826	70	
2	206	140	
3	91	210	
4	51	281	