




DP-RMSP-MC5

MACA


Luminaire Information

System power	5W
CCT	2700K, 3000K, 3500K, 4000K, TUNABLE WHITE
CRI / Ra	±90Ra
Fixture lumen output	250lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (15°, 24°, 36°)
UGR level	<14
Installation	Recessed
IP rate	IP20 / IP54
Fixture	Adjustable

Product Dimension



DP-RMSP-MC5
Fixed



DP-RMSP-MC5(TL)
Trimless

Light Engine Information

LED type	COB
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	150mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option




Black White


Light Throw

DP-RMSP-MC5 3000K 90Ra

	h(m)	E(lx)	D(cm)
1	602	37	
2	150	75	
3	66	112	
4	37	150	



	h(m)	E(lx)	D(cm)
1	343	53	
2	85	107	
3	38	161	
4	21	215	



	h(m)	E(lx)	D(cm)
1	185	69	
2	46	139	
3	20	209	
4	11	279	

