




DP-RMSP-MN10

MONNA

Luminaire Information

System power	10W
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 2700K - 6500K
CRI / Ra	±96Ra
Fixture lumen output	880lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (9°, 15°, 23°, 36°, 55°)
UGR level	<19
Installation	Recessed
IP rate	IP20
Fixture	Fixed

Product Dimension



Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information


Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	250mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option



Black

LED Chip Option




FULL SPECTRUM


Light Throw

DP-RMSP-MN10 3000K 96Ra


	h(m)	E lx)	D(cm)
1	5634	30	
2	1408	60	
3	626	90	
4	352	121	




	h(m)	E lx)	D(cm)
1	3394	43	
2	848	87	
3	377	131	
4	212	175	



	h(m)	E lx)	D(cm)
1	1693	65	
2	423	131	
3	188	196	
4	105	262	



	h(m)	E lx)	D(cm)
1	670	103	
2	167	207	
3	74	311	
4	41	414	



MONNA FIXTURE ACCESSORIES

	Code No DP-302		 68mm	 Dark Chrome  Silver  Black  White  Pin hole
	Code No DP-302A		 68mm	 Dark Chrome  Silver  Black  White  Oval hole
	Code No DP-310		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-310A		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-302CT		 68mm	 Dark Chrome  Silver  Black  White  Pin hole
	Code No DP-302ACT		 68mm	 Dark Chrome  Silver  Black  White  Oval hole
	Code No DP-310CT		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-310ACT		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-314A		 75x143mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-321A		 75x215mm	 Dark Chrome  Silver  Black  White  Square hole

-  Linear Spread Filter
-  Soft Filter
-  IP54 Glass Protector
-  Honeycomb Louver
-  Anti-glare Ring

Lens Accessories Option