




DP-RMSP-MN5

MONNA

Luminaire Information

System power	5W
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 2700K - 6500K
CRI / Ra	±96Ra
Fixture lumen output	440lm
Material	Aluminum
Surface finish	Powder coating
Optics	Lens (9°, 15°, 23°, 36°, 55°)
UGR level	<19
Installation	Recessed
IP rate	IP20
Fixture	Fixed

Product Dimension



Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Remote
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	135mA
Dimming system	ON-OFF / TRIAC / 1-10V / DALI

Color Option







Black

LED Chip Option



Light Throw

DP-RMSP-MN5 3000K 96Ra



MONNA FIXTURE ACCESSORIES

	Code No DP-302		 68mm	 Dark Chrome  Silver  Black  White  Pin hole
	Code No DP-302A		 68mm	 Dark Chrome  Silver  Black  White  Oval hole
	Code No DP-310		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-310A		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-302CT		 68mm	 Dark Chrome  Silver  Black  White  Pin hole
	Code No DP-302ACT		 68mm	 Dark Chrome  Silver  Black  White  Oval hole
	Code No DP-310CT		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-310ACT		 75x75mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-314A		 75x143mm	 Dark Chrome  Silver  Black  White  Square hole
	Code No DP-321A		 75x215mm	 Dark Chrome  Silver  Black  White  Square hole

-  Linear Spread Filter
-  Soft Filter
-  IP54 Glass Protector
-  Honeycomb Louver
-  Anti-glare Ring

Lens Accessories Option