





DP-TSRP-OP12

OPRA


Luminaire Information

System power	12W
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, TW
CRI / Ra	±95Ra
Fixture lumen output	1050lm
Material	Aluminum
Surface finish	Textured powder coating
Optics	Lens (15°, 24°, 36°, 55°)
UGR level	<17
Installation	Track mounted, surface mounted, recessed mounted
IP rate	IP20

Product Dimension



DP-TSRP-OP12(S)
Surface



DP-TSRP-OP12(R)
Recessed

Light Engine Information

LED type	COB (Bridgelux)
LED voltage	36V
SDCM	2 SDCM / 3 SDCM

Driver Information

Driver type	Built-in
Input voltage	220-240 VAC
Output voltage	30-42 VDC
Output current	300mA
Dimming system	ON-OFF / TRIAC

Track Adapter



(2-wire 1-circuit)



(3-wire 1-circuit)



(4-wire 3-circuit)

Accessories



Honeycomb louver

Color Option



Black White

Light Throw

DP-TSRP-OP12 3000K 95Ra

	h(m)	E(lx)	D(cm)
1	3377	28	
2	844	57	
3	375	86	
4	211	114	

	h(m)	E(lx)	D(cm)
1	2802	42	
2	700	84	
3	311	127	
4	175	169	

	h(m)	E(lx)	D(cm)
1	1251	65	
2	312	131	
3	139	197	
4	78	263	

	h(m)	E(lx)	D(cm)
1	489	108	
2	122	216	
3	54	324	
4	30	432	