





DP-TSRP-OP6

### OPRA


#### Luminaire Information

|                      |  |
|----------------------|--|
| System power         | 6W   |
| CCT                  | 2700K, 3000K, 3500K, 4000K, 5000K, 6000K, TW     |
| CRI / Ra             | ±95Ra  |
| Fixture lumen output | 400lm  |
| Material             | Aluminum   |
| Surface finish       | Textured powder coating                          |
| Optics               | Lens (15°, 24°, 36°, 55°)                        |
| UGR level            | <17  |
| Installation         | Track mounted, surface mounted, recessed mounted |
| IP rate              | IP20   |

#### Product Dimension



DP-TSRP-OP6(S)  
Surface



DP-TSRP-OP6(R)  
Recessed

#### Light Engine Information

|             |                 |
|-------------|-----------------|
| LED type    | COB (Bridgelux) |
| LED voltage | 36V             |
| SDCM        | 2 SDCM / 3 SDCM |

#### Driver Information

|                |                |
|----------------|----------------|
| Driver type    | Built-in       |
| Input voltage  | 220-240 VAC    |
| Output voltage | 30-42 VDC      |
| Output current | 130mA          |
| Dimming system | ON-OFF / TRIAC |

#### Track Adapter



(2-wire 1-circuit)



(3-wire 1-circuit)



(4-wire 3-circuit)

#### Accessories



Honeycomb louver

#### Color Option



Black White

#### Light Throw

DP-TSRP-OP6 3000K 95Ra

